

基本資料

主題名稱	卡威科技 RFID CHIP 比較表規格圈說明			
聯絡人		電話/分機		傳真
公司名稱		E_mail		
地址				

EM 125KHz 感應卡片規格

Brand	Part Number	Frequency	Description	Remark
EM-Marine	EM4005/EM4105	134KHz	Read only,128 Bit	EM4105 with Gold Bumps
	EM4100/EM4102	125KHz	Read only,64 Bit	EM4102 with Gold Bumps
	EM4450/EM4550	125KHz	R/W,1K Bit	EM4550 with Gold Bumps
	EM4469/EM4569	125~134KHz	R/W,512 Bit	EM4569 with Gold Bumps
Atmel	T5557	125KHz	R/W,330 Bit	ISO 11784/85 Compatible
	ATA5567	125KHz	R/W,330 Bit	ISO 11784/85 Compatible
NXP (Philips)	MIFARE Ultralight	13.56MHz	R/W,512 Bit	ISO 14443 Type A
	MIFARE Classic S50	13.56MHz	R/W,1K Byte	ISO 14443 Type A
	MIFARE Classic S70	13.56MHz	R/W,4K Byte	ISO 14443 Type A
	MIFARE DESFire	13.56MHz	R/W,4K Byte	ISO 14443 Type A
	I.CODE SLI	13.56MHz	R/W,1024 Bit	ISO 15693
	I.CODE SLI-S	13.56MHz	R/W,2048 Bit	ISO 15693, EPC
	HITAG 1	125KHz	R/W,2048 Bit	
	HITAG 2	125KHz	R/W,256 Bit	
	HITAG S	125KHz	R/W,32/256/2048 Bit	ISO 11784/11785; ISO 14223/1
LEGIC	MIM256	13.56MHz	R/W,256 Byte	
	MIM1024	13.56MHz	R/W,1024 Byte	

Infineon	my-d SRF 55V02S	13.56MHz	R/W,2K Bit	ISO 15693
	my-d SRF 55V10S	13.56MHz	R/W,10K Bit	ISO 15693
	SLE66R35	13.56MHz	R/W,1K Byte	ISO 14443 Type A
ST	SRIX4K	13.56MHz	R/W,4096 Bit	ISO 14443 Type B
	LRI64	13.56MHz	R/W,64 Bit(UID)	ISO 15693 with WORM User Area
	LRI2K	13.56MHz	R/W,2048 Bit	ISO 15693
TI	Tag-it HF-I Standard	13.56MHz	R/W,256 Bit	ISO 15693
	Tag-it HF-I Pro	13.56MHz	R/W,256 Bit	ISO 15693
	Tag-it HF-I Plus	13.56MHz	R/W,2048 Bit	ISO 15693
Inside	PicoPass 32KS	13.56MHz	R/W,32 Bit	ISO 15693 & 14443B
Felica	RCS919	13.56MHz	R/W,576 Byte	